

Thermo Roll Fixed Windows

Full-view heavy commercial aluminum windows with top air and water infiltration performance.

Durability

- Frame corners are joined with four stainless steel screws (7000 series)
- Frame corners are joined with corner gussets and crimped (6200 and 5000 series)
- Frame corners are joined with three stainless steel screws (12000 and 2000 series)

Versatility

- Panel depths up to 1" are easily accommodated.
- Optional dual glazing permits thermal glazing of polycarbonate
- Optional dual glazing permits inserting internal blinds
- Vertical or horizontal stacking

Standards

- 1" insulating glass
- Interior snap-in glazing bead
- Internal weep system
- Sub-frames, mullions and transom members

Options

- Integral mullions (specify sill/left jamb-to-CMR dimension)
- Dual glazed (split vent): maximum 3/4" exterior and interior panel
- Triple glazed: 3/4" exterior; interior pane; maximum 1/4"
- Exterior, internal, or true muntins
- Internal blinds

Thermo Roll's Design Flexibility Engineering Allows for the Windows to be Fabricated with the Mosaic or Universal Frame for Longevity & Lower Costs.



Model Number	Test Size	Rating	Air Infiltration	Water	Uniform
TRS-5009	60x99	F-HC65	6.24 PSF	8.0 PSF	60.0 PSF
TRS-6209	60x99	F-AW65	6.24 PSF	8.0 PSF	60.0 PSF
TRS-7009	60x99	F-HC65	6.24 PSF	8 PSF	60 PSF
TRS-2009	60x99	F-HC50	6.24 PSF	8 PSF	55 PSF
TRS-12009	60x99	F-C55	6.24 PSF	8 PSF	55 PSF

THERMOROLL
WINDOW MANUFACTURING

77 Bennington Ave., Freeport, NY 11520
800-945-2545 • Fax: 631-643-3559 • www.thermoroll.com