

Thermo Roll Out-Swing Casement

An ideal window for maximum view, ventilation and egress. Unique Design allows for Roto Operator With Special Hinge that permits window washing from the inside.

Strength

- Frame and vent members are double tubular extrusions
- Corners are reinforced with gussets before crimping
- Hardware is fastened with screws through two walls

Durability

- Glazing gasket is Neoprene for ozone/UV resistance
- Vent-to-frame gaskets are EPDM to prevent shrinkage
- Hinges are stainless steel for corrosion resistance

Standards

- 1" insulating glass; interior bead glazing adapter for fixed
- Concealed adjustable stainless-steel 4-bar hinges
- White bronze cam handles and strikes
- All frames and vents thermally improved using latest technology

Options

- Dual-glazed (split vent): maximum 3/4" exterior and interior
- Triple-glazed (split vent): 3/4" insulating glass exterior and maximum 1/4" Interior
- Root operator
- Butt hinges: multi-point lock
- Integral mullions (specify sill/left jamb-to-CMR dimension)
- Insect screens: interior full-width or with wickets
- Exterior or internal muntins
- Internal blinds
- Exterior washability feature

Thermo Roll's Design Flexibility Engineering Allows for the Windows to be Fabricated with the Mosaic or Universal Frame for Longevity & Lower Costs.



Model Number	Test Size	Rating	Air Infiltration	Water	Uniform
TRS-6202	36x60	C-AW40	6.2 PSF	8.0 PSF	60.0 PSF
TRS-7002	32x60	C-AW50	8.2 PSF	8.0 PSF	87.5 PSF

THERMO ROLL
WINDOW MANUFACTURING

77 Bennington Ave., Freeport, NY 11520
800-945-2545 • Fax: 631-643-3559 • www.thermoroll.com